

The `lectureslides` Package*

Taihao Zhang
t@taihao.de

1st March 2022

When studying, there frequently occurs the situation where one uses `Ctrl+F` many times to search for a keyword in all the lecture slides. Throughout an entire semester, there can be a large number of PDFs that would need to be searched.

This package allows for easily combining individual PDFs into a large one, indexing each with a title that PDF viewers can display. `lectureslides` also provides a table of contents.

Usage

In general, usage of `lectureslides` works as follows:

```
\documentclass{article}
\usepackage{lectureslides}
\begin{document}
  \course{Engineering Mechanics}
  \tableofcontents

  \lecture{Introduction to EM}{intro}
  \lecture{Centre of gravity}{centre}
\end{document}
```

`\course` Acts as the title on the cover page, used in the form `\course[]{Engineering Mechanics}`. The optional argument specifies the footnote text, which otherwise defaults to **Compiled \today**. This text adapts to an `ngerman` setting in `babel`.¹

*This document corresponds to `lectureslides` version 1.0 / 2022-03-01.

¹This requires that this package is loaded after `babel`.

`\lecture` Inserts one set of lecture slides. This command takes two mandatory arguments in the following form:

```
\lecture{Title of this lecture}{pdf_file_name}
```

Two optional arguments can specify the range of slides that need to be included. For example, to include slides 10–35 of `intro.pdf`:

```
\lecture{Introduction to EM}[10][35]{intro}
```

Either optional argument can be left empty. To include slides up to slide number 35:

```
\lecture{Introduction to EM}[] [35]{intro}
```

To include slides from slide number 10 til the end:

```
\lecture{Introduction to EM}[10] []{intro}
```

Internally, this command calls `\lecturetitle` and `\lectureslides`.

`\tableofcontents` Prints a table of contents of all lectures. Each `\lecture` (and consequently `\lecturetitle`) gets its own entry here. `\tocline` customises the appearance.

Option

`landscape` `landscape` is the default orientation if no option is passed, as lecture slides are most often given out in this format. `portrait` can be used instead to insert slides in portrait orientation.

Advanced

`\lecturetitle` Declares a new set of slides, but doesn't insert any PDF pages yet. When followed by `\lectureslides`, an actual entry in the table of contents gets created.

```
\lecturetitle{Title of this lecture}
```

`\lectureslides` Inserts a set of slides from a given PDF. Optional arguments specify the range of slides to be included.

```
\lectureslides[10][35]{pdf_file_name}
```

Multiple `\lectureslides` can be stringed together to include slides from different PDFs. These will then all be organised under the last preceding `\lecturetitle`.

`\tocline` Determines how the lecture title appears in the table of contents (ToC). Putting the following in the preamble redefines this, for example:

```
\renewcommand{\tocline}[1]{%
    Semana \arabic{section}: #1%
}
```

Alternatively, `\renewcommand{\tocline}[1]{#1}` omits the numbering, putting only the title in the ToC.